

FO patch panel OV-T

19"/1U, unloaded
without front plate, telescopic slides,
depth-adjustable mounting



Fibre optic patch panel OV-T, 19"/1U, without front plate,
with telescopic slides, depth-adjustable mounting

DESCRIPTION

For the termination of fibre optic cables - maximum of 96 fibres.
Applicable with a wide range of front plates / connector systems (see OV-T / OV-S 1U accessories).

SCOPE OF DELIVERY

Box, strain relief cable gland, splice tray holder and
Please order the front plate separately.

GENERAL PROPERTIES

Housing:	metallic, with telescopic slides and locking mechanism
Rack mounting:	depth-adjustable mounting of box (5 steps, maximum 50 mm) due to the adjustable 19" mounting brackets
Colour of mounting brackets (variants):	similar to RAL 7035, similar to RAL 9005 or stainless steel
Capacity:	up to 96 fibres
Strain relief:	with cable tie and screwed cable gland or cable distributor
Cable entry:	rear left and right (two big openings, with pre-stamped cable entries 2x M15, 1x M20 – these pre-stamped holes can be opened as necessary)
Dimensions:	19"/1U, depth 254 mm

VERSIONS

Article No.	Product	Colour	PU
41555300ZY	OV-T telescopic 1U	light grey	1 pc.
41555400ZY	OV-T telescopic 1U	silver	1 pc.
41555500ZY	OV-T telescopic 1U	black	1 pc.