

FO patch panel OV-T

19"/1U, sin cargar
sin placa frontal, guías telescópicas,
montaje de profundidad ajustable



Fibre optic patch panel OV-T, 19"/1U, without front plate,
with telescopic slides, depth-adjustable mounting

DESCRIPCIÓN

Para la terminación de los cables de fibra óptica - máximo de 96 fibras.
Aplicable con una amplia gama de placas frontales / sistemas de conectores (ver accesorios OV-T / OV-S 1U).

FORMA DE SUMINISTRO

Caja, prensaestopas de alivio de tensión, soporte de la bandeja de empalme y
Por favor, pida la placa frontal por separado.

PROPIEDADES GENERALES

Housing:	metallic, with telescopic slides and locking mechanism
Rack mounting:	depth-adjustable mounting of box (5 steps, maximum 50 mm) due to the adjustable 19" mounting brackets
Colour of mounting brackets (variants):	similar to RAL 7035, similar to RAL 9005 or stainless steel
Capacity:	up to 96 fibres
Strain relief:	with cable tie and screwed cable gland or cable distributor
Cable entry:	rear left and right (two big openings, with pre-stamped cable entries 2x M15, 1x M20 – these pre-stamped holes can be opened as necessary)
Dimensions:	19"/1U, depth 254 mm

VERSIONES

N° de artículo	Producto	Color	UE
41555300ZY	OV-T telescopic 1U	gris claro	1 pza.
41555400ZY	OV-T telescopic 1U	plateado	1 pza.
41555500ZY	OV-T telescopic 1U	negro	1 pza.