

Product overview and selection criteria
for Datwyler elevator cables

Article no.	Type	Control cores					Data elements (see page 36/37)													Standards														
		0.75	1.00	1.50	2.00	2.50	4 x 2 x AWG 26	7702 flex 4P	7954/2-F	7345-F	6651-F	6651/2-F	7067/2-F *	7954/2-F	6651/3-H	6651-F	6651/2-F	6651/3-F	7067/2-F *		7954/2-F	8607-F	6347/2-F	6347/3-F	8504-F	GF-2314	GF-2314	HF-2122-F	HF-2123-F					
		Dimensions in mm ²																																
FH – PVC flat cable – high rise – supported – up to 400 m shaft height																		page 24/25																
157219	7877-F	40																																
185284	7877-F	60																																
161448	8292-F	40																				2							1					
176846	8490-F	30																											1					
184645	8846-F	30																																
192528	8893-F	12																												1				
FH Module Concept – PVC flat cable – supported – up to 400 m shaft height																		page 26/27																
184646	8847-F	16	7	5																						2	2							
185372	8847-F	18		10																							2							
177860	8687-F	40						8														3												
187125	8847-F	16	7	5																						4								
186276	8858-F	30	12					7																3										
187102	8687-F	30		5																														
188337	8680-F	20		10																														
192527	8892-F	24	6	20																								4						
FL – Low Fire Hazard – unsupported – up to 80 m shaft height																		page 28/29																
191110	8511-F	12																																
191111	8636-F	12																																
185125	8511-F	18						3																										
191112	8511-F	24																																
182205	8827-F	14		3	4																													
191113	8582-F	24																												1				
190491	8582-F		2					8																						1				
FM – Low Fire Hazard – supported – up to 150 m shaft height																		page 30/31																
185127	8622-F	12																														1		
185124	8696-F	12																						1										
184674	8849-F							12																										
191094	8872-F	14		3	4																													
FH – Low Fire Hazard – supported – up to 400 m shaft height																		page 32/33																
185126	8585-F	30																																
192313	8880-F	12																												24				
FH Module Concept – Low Fire Hazard – up to 400 m shaft height																		page 34/35																
191114	8859-F	30	12					7																										
191483	8866-F	6	7	10																							4	2						
192314	8881-F	24	6	20																														
192236	8839-F			35																														
192342	8866-F	42																												12				
		Standards:				EN 50214				JIS C 3408																								

* unshielded